



DURAPLUG®

RANGE INTRODUCTION

The Duraplug® range of heavy duty products has become a virtual byword for durability, strength and reliability.

Duraplug® offers a wide range of products including a complete range of safety extension leads featuring rubber covered plugs, extension leads, trailing sockets, lead connectors and cable couplers. All Duraplug® products are made from top quality, high impact resistant materials such as ABS/polycarbonate and rubber.

FEATURES & BENEFITS

- Produced with top quality, high impact resistant materials such as ABS/polycarbonate and rubber
- Sockets have visible red nylon shutters
- Lead connectors have retaining lugs to prevent accidental disconnection
- All internal parts of trailing sockets are retained in the base for ease of wiring



Technical Hotline
+44 (0)1268 563720

Duraplug®

WIRING DEVICES
PORTABLE POWER

Heavy Duty Extension Leads

4 WAY
13 AMP



EXL135WHI EXL135BLK

13 AMP



EXL136WHI EXL136BLK

13 AMP



EXL137WHI EXL137BLK

Heavy Duty Portable Socket

4 WAY
FILTERED
13 AMP



744WHI

EXL135WHI
EXL135BLK
13A WITH FUSE, NEON AND
2 METRE CABLE

1
1

Fitted with approved PVC insulated cable of appropriate core size for maximum 13A rating and a Duraplug® rubber plug.
The sockets are manufactured in high impact ABS/Polycarbonate.
Fitted with a fuse carrier and 13A fuse to BS 1362
BS 1363/A-2:1995
BS EN 50525-2-11 – Cable

EXL136WHI
EXL136BLK
13A WITH SWITCH, NEON AND
2 METRE CABLE

1
1

Fitted with approved PVC insulated cable of appropriate core size for maximum 13A rating and a Duraplug® rubber plug.
The sockets are manufactured in high impact ABS/Polycarbonate.
BS 1363/A-2:1995
BS EN 50525-2-11 – Cable

EXL137WHI
EXL137BLK
13A WITH FUSE, SWITCH, NEON AND
2 METRE CABLE

1
1

Fitted with approved PVC insulated cable of appropriate core size for maximum 13A rating and a Duraplug® rubber plug.
The sockets are manufactured in high impact ABS/Polycarbonate.
BS 1363/A-2:1995
BS EN 50525-2-11 – Cable

744WHI
13A WITH SWITCH, NEON AND FUSE

1

Fitted with a fuse carrier and 13A fuse to BS 1362.
Manufactured in high impact ABS/Polycarbonate.
Can also be wall mounted.
Fitted with a fuse carrier and 13A fuse to BS 1362
DIMENSIONS
317 x 68 x 31mm
SPECIFICATION
Max. Power 3.14kW
Response time (Varistor) better than 20ns
BS 1363/A-2:1995

Duraplug®

mkelectric.co.uk



Heavy Duty Portable Socket

4 WAY
13 AMP



FC4134WHI FC4134BLK

13 AMP



FC4135WHI FC4135BLK

13 AMP



FC4136WHI FC4136BLK

Heavy Duty Trailing Sockets

13 AMP



FC133WHI



FC133ORG



FC133BLK



FCT133WHI



FCT133BLK



FC153BLK

FC4134WHI 1
FC4134BLK 1
13A WITH FUSE AND NEON

Manufactured in high impact ABS/
Polycarbonate incorporating optional
wall mounting holes and equal length
wire stripping.

DIMENSIONS
317 x 68 x 31mm
BS 1363/A-2:1995

FC4135WHI 1
FC4135BLK 1
13A WITH SWITCH AND NEON

Manufactured in high impact ABS/
Polycarbonate incorporating optional
wall mounting holes and equal length
wire stripping.

DIMENSIONS
317 x 68 x 31mm
BS 1363/A-2:1995

FC4136WHI 1
FC4136BLK 1
13A WITH SWITCH, FUSE
AND NEON

Manufactured in high impact ABS/
Polycarbonate incorporating optional
wall mounting holes and equal length
wire stripping.

DIMENSIONS
317 x 68 x 31mm
BS 1363/A-2:1995

FC133WHI 10
FC133BLK 10
FC133ORG 10
13A SINGLE OUTLET

Manufactured from tough
Polypropylene with rubber cover. All
internal component parts are retained
in the base for ease of wiring.

DIMENSIONS
79 x 62 x 29mm
BS 1363/A-2:1995

FCT133WHI 10
FCT133BLK 10
FCT133ORG 10
13A TWIN OUTLET

FC153BLK 10
15A SINGLE OUTLET
ROUND PIN

FCT133
Manufactured from tough
Polypropylene with rubber cover. All
internal component parts are retained
in the base for ease of wiring.
BS 1363/A-2:1995

FC153
Rubber cover.
BS 546:1950
DIMENSIONS
FCT133 80 x 125 x 29mm
FC153 67 x 53 x 33mm



Technical Hotline
+44 (0)1268 563720

Duraplug®

WIRING DEVICES
PORTABLE POWER

Lead Connectors

TWO & THREE PIN
10 AMP


SPARES
10 AMP



LCP102BLK



LCP102SBLK



LCP102SBLK



LCP103BLK



LCP102PBLK



LCP103SBLK



LCP103PBLK



LCP103PWHI

Rubber Plugs

Cable Couplers



PF133WHI



PF133ORG



P153BLK



CCP53BLK



CCP153BLK



LCP102BLK 10
LCP102ORG 10
TWO PIN 10A PLUG
AND SOCKET
LCP103WHI 10
LCP103BLK 10
THREE PIN 10A PLUG
AND SOCKET

This range of connectors provides a safe and easy method of extending power cables and electrical tools and appliances. With rubber cover and polypropylene inserts with integral cable grips. Retaining lugs prevent accidental disconnection.

Two pin versions are only for use with double insulated Class 2 appliances. Three pin versions must be used with earthed appliances.

DIMENSIONS

40 x 25 x 80mm
BS 5733:2010

Comply with IP44 Ingress Protection rating to BS EN 60529:1992

LCP102PBLK 10
LCP102PORG 10
10A PLUG TWO PIN
LCP102SBLK 10
LCP102SORG 10
10A SOCKET TWO PIN

BS 5733:2010

Comply with IP44 Ingress Protection rating to BS EN 60529:1992

LCP103PWHI 10
LCP103PBLK 10
10A PLUG THREE PIN
LCP103SWHI 10
LCP103SBLK 10
10A SOCKET THREE PIN

BS 5733:2010

Comply with IP44 Ingress Protection rating to BS EN 60529:1992

P53BLK 10
5A ROUND PIN
PF133WHI 10
PF133ORG 10
PF133BLK 10
FITTED WITH 13A FUSE
P153BLK 10
15A ROUND PIN

PF133

With rubber cover. Available with alternative fuse ratings to special order only. Approved by ASTA Licence no.470 BS 1363/A-1:1995

P53BLK

Manufactured in rubber

P153BLK

With rubber cover and ABS/Polycarbonate base. BS 546:1950

CCP53BLK 1
5A PLUG & SOCKET
CCP153BLK 1
15A PLUG & SOCKET
CCP133PBLK 1
SPARE 13A PLUG

These splashproof couplers are a rugged means of connecting cables in industrial and commercial environments. Fitted with heavy duty cable clamps, tapered cable entry and fuse (13A version only).

DIMENSIONS

Diameter x Length
CCP53 60 x 173mm
CCP133 65 x 182mm
CCP153 68 x 180mm
BS 5733:2010 (BS 1363 Pin centres for 13A versions)
BS 5733:2010 (BS 546 Pin centres for 5A and 15A versions)

Plugs and Adaptors



Established range of plugs and adaptors. The established names of Safetyplug™ and Toughplug™ strengthen MK's reputation for high quality products with the accent on safety and quality.

Safetyplugs

NON STANDARD



646WHI	10
646CHA	10
FITTED WITH 13A FUSE	
64603WHI	10
FITTED WITH 3A FUSE	
645NIP	100
SECRET SCREW FOR SAFETYPLUG AND TOUGHPLUG	
644ZIC	10
KEY FOR SECRET SCREW	

See page 222 for spare fuse links.
BS 1363-1:1995

647WHI	10
647CHA	10
FITTED WITH 13A FUSE	

See page 222 for spare fuse links.
T shaped earth pin for use with MK non-standard 13A sockets only.
BS 1363-1:1995 (where relevant)

Toughplugs

655WHI	10
FITTED WITH 13A FUSE	
65503WHI	10
FITTED WITH 3A FUSE	
655BLK	10
655ORG	10
655RED	10
FITTED WITH 13A FUSE	
655D8WHI	10
655D8RED	10
MARKED 'HOSPITAL PROPERTY' FITTED WITH 13A FUSE	

See page 222 for spare fuse links.
BS 1363/A-1:1995



Technical Hotline
+44 (0)1268 563720

Plugs and Adaptors

Round Pin Plugs

Plug Adaptors



505WHI



515WHI



641WHI



690WHI



692WHI



696WHI



698PPK

- 502WHI** 10
2A
- 505WHI** 10
5A
- 515WHI** 10
15A RESILIENT COVER
- 641WHI** 10
5A FUSED
- 643WHI** 10
15A FITTED WITH 5A FUSE

- 690WHI** 5
13A WITH 1 X 13A AND
1 COMBINED 16A UNIVERSAL
AND GERMAN TYPE 2P+E
SOCKET OUTLET
FUSED 13A

- 692WHI** 5
13A WITH
3 X 13A SOCKET OUTLETS
FUSED 13A
- 696WHI** 5
13A WITH
2 X 13A SOCKET OUTLETS
UNFUSED
- 698PPK** 10
13A WITH
1 X 1A SHAVEN SOCKET OUTLET
FUSED 1A

See page 222 for spare fuse links to
BS 646.
BS 546:1950

BS 1363-3:1995 (where relevant)

BS 1363-3:1995 (where relevant)